

Breather

DATASHEET

Glass laminating material

Product description

This breather of white wool is suitable for use in an autoclave-free oven or a high pressure autoclave environment. It frames the glass very easy and allows a constant uniform vacuum flow that protects the interlayer.

Performance features

- Very flexible.
- Extremely porous.
- Maximum processing temperature of 205° C.

Application

- Used around the edge of the glass for excellent air transmission during the laminating process.



Breather

Interlayer

Interlayer decorative

Interlayer active

Vacuum bag

Laminating supplies

Laminating tools

Spares

Breather

DATASHEET

Glass laminating material

Product specifications

Standard widths	75 mm, 150 mm, 1520 mm; available up to 6 mtr wide.
Standard length	50 mtr.
Cut shapes/slit widths	On request .
Maximum cure temperature	205 °C.
Color	White.
Fiber	100% polyester.
Weight	330 g/m ² .

Notice: Breather has no release characteristics and should be separated from the laminated glassd by a suitable porous release fabric or film. Breather is not intended to be used as a breather material alone.

Storage & Handling

- No special storage conditions required.

Caution

- Handle this product according to your company's guidelines, health and safety regulations.

Interlayer
Interlayer decorative
Interlayer active
Vacuum bag
Laminating supplies
Laminating tools
Spares